

**AMENDMENTS TO THE CLAIMS**

Claims 1-58. (Canceled)

Claim 59. (Currently Amended) A digital video signal recorder capable of inhibiting unauthorized copying of an analog video signal, comprising:

an input terminal for receiving said analog video signal, said analog video signal including a copy protection signal;

analog-to-digital converting means for converting said analog video signal to digital video data;

compression means for compressing said digital video data to generate compressed video data;

detecting means for detecting said copy protection signal included in said analog video signal;

generating means for generating copy management information according to a state of said copy protection signal detected by said detecting means;

appending means for appending said copy management information to said compressed video data; and

recording means for recording said compressed video data with appended copy management information, said copy management information being recorded at a pre-set position of a record medium;

whereby said copy management information is digital information that is generated based on an analog signal; said copy management information including an

indicator of whether copying of only digital video data generated from the received analog video signal is inhibited or copying of both digital and analog video data generated from the received analog video signal is inhibited.

Claim 60. (Previously Presented) The recorder according to claim 59, wherein said copy protection signal is a signal coded with plural bits, is located at a pre-set position of said analog video signal and is indicative of a copy generation limitation.

Claim 61. (Previously Presented) The recorder according to claim 60, wherein said pre-set position of said analog video signal is a pre-set horizontal period within a vertical blanking period of said analog video signal.

Claim 62. (Previously Presented) The recorder according to claim 61, wherein said pre-set horizontal period is the twentieth horizontal period within said vertical blanking period.

Claim 63. (Previously Presented) The recorder according to claim 59, wherein said pre-set position of said record medium is located within a data area and/or a lead-in area of said record medium.

Claim 64. (Previously Presented) The recorder according to claim 63, wherein said pre-set position of said record medium is located within a header portion which is within said data area of said record medium.

Claim 65. (Previously Presented) The recorder according to claim 59, wherein said digital video data is partitioned into units and said copy management information is located in at least one of said units.

Claim 66. (Previously Presented) The recorder according to claim 59, wherein said record medium is an optical disc, a magneto-optical disc, a magnetic hard disk or an integrated circuit (IC) memory card.

Claim 67. (Previously Presented) The recorder according to claim 59, wherein said analog video signal is an analog video signal having a combination signal of plural pseudo synchronization pulses and plural white peak signals across plural horizontal periods in a vertical blanking period of said analog video signal.

Claim 68. (Previously Presented) The recorder according to claim 59, wherein said analog video signal is an analog color video signal having an associated color burst signal and wherein the phase of at least a portion of said color burst signal is changed from an original state.

Claim 69. (Previously Presented) The recorder according to claim 68, wherein said copy protection signal is a signal coded with plural bits, is located at a pre-set position of said analog video signal and is indicative of a limitation on recording.

Claim 70. (Currently Amended) A digital video signal recorder capable of inhibiting unauthorized copying of an analog video signal, comprising:

an input terminal for receiving said analog video signal, said analog video signal including a copy protection signal;

analog-to-digital converting means for converting said analog video signal to digital video data;

compression means for compressing said digital video data to generate compressed video data;

detecting means for detecting said copy protection signal included in said analog video signal;

generating means for generating copy management information according to a state of said copy protection signal detected by said detecting means;

scrambling means for generating scrambled video data by scrambling said compressed video data according to key information; and

recording means for recording said scrambled video data with said key information, said key information being recorded at a pre-set position of a record medium;

whereby said copy management information is digital information that is generated based on an analog signal; said copy management information including an indicator of whether copying of only digital video data generated from the received analog video signal is inhibited or copying of both digital and analog video data generated from the received analog video signal is inhibited.

Claim 71. (Previously Presented) The recorder according to claim 70, wherein said pre-set position of said record medium is located within a data area and/or a lead-in area of said record medium.

Claim 72. (Previously Presented) The recorder according to claim 71, wherein said pre-set position of said record medium is located within a header portion which is within said data area of said record medium.

Claim 73. (Previously Presented) The recorder according to claim 72, wherein said digital video data is partitioned into units and said key information is located in at least one of said units.

Claim 74. (Previously Presented) The recorder according to claim 70, wherein said key information corresponds to bit sequence data used to implement the scrambling.

Claim 75. (Currently Amended) A digital video signal recorder capable of inhibiting unauthorized copying of an analog video signal, comprising:

an input terminal for receiving said analog video signal, said analog video signal including a copy protection signal;

analog-to-digital converting means for converting said analog video signal to digital video data;

compression means for compressing said digital video data to generate compressed video data;

detecting means for detecting said copy protection signal included in said analog video signal;

generating means for generating copy management information according to a state of said copy protection signal detected by said detecting means;

scrambling means for generating scrambled video data by scrambling said compressed video data according to key information;

appending means for appending said copy management information to said scrambled video data; and

recording means for recording said scrambled video data with said copy management information and said key information, said copy management information and said key information being recorded at a pre-set position of a record medium;

whereby said copy management information is digital information that is generated based on an analog signal; said copy management information including an indicator of whether copying of only digital video data generated from the received analog video signal is inhibited or copying of both digital and analog video data generated from the received analog video signal is inhibited.

Claim 76. (Previously Presented) The recorder according to claim 75, wherein said copy protection signal is a signal coded with plural bits, is located at a pre-set position of said analog video signal and is indicative of a copy generation limitation.

Claim 77. (Previously Presented) The recorder according to claim 75, wherein said pre-set position of said record medium is located within a data area and/or a lead-in area of said record medium.

Claim 78. (Previously Presented) The recorder according to claim 77, wherein said pre-set position of said record medium is located within a header portion which is within said data area of said record medium.

Claim 79. (Previously Presented) The recorder according to claim 75, wherein said key information corresponds to bit sequence data used to implement the scrambling.

Claim 80. (Currently Amended) A digital video signal recording method through which unauthorized copying of an analog video signal can be inhibited, comprising the steps of:

receiving said analog video signal, said analog video signal including a copy protection signal;

performing an analog-to-digital conversion on said analog video signal to generate digital video data;

compressing said digital video data to generate compressed video data;

detecting said copy protection signal included in said analog video signal;

generating copy management information according to a state of said copy protection signal detected in said step of detecting;

appending said copy management information to said compressed video data; and

recording said compressed video data with appended copy management information, said copy management information being recorded at a pre-set position of a record medium;

whereby said copy management information is digital information that is generated based on an analog signal; said copy management information including an indicator of whether copying of only digital video data generated from the received analog video signal is inhibited or copying of both digital and analog video data generated from the received analog video signal is inhibited.

Claim 81. (Previously Presented) The recording method according to claim 80, wherein said copy protection signal is a signal coded with plural bits, is located at a pre-set position of said analog video signal and is indicative of a copy generation limitation.

Claim 82. (Previously Presented) The recording method according to claim 80, wherein said pre-set position of said analog video signal is a pre-set horizontal period within a vertical blanking period of said analog video signal.

Claim 83. (Previously Presented) The recording method according to claim 82, wherein said pre-set horizontal period is the twentieth horizontal period within said vertical blanking period.



Claim 84. (Previously Presented) The recording method according to claim 80, wherein said pre-set position of said record medium is located within a data area and/or a lead-in area of said record medium.

Claim 85. (Previously Presented) The recording method according to claim 84, wherein said pre-set position of said record medium is located within a header portion which is within said data area of said record medium.

Claim 86. (Previously Presented) The recording method according to claim 80, wherein said digital video data is partitioned into units and said copy management information is located in at least one of said units.

Claim 87. (Previously Presented) The recording method according to claim 80, wherein said record medium is an optical disc, a magneto-optical disc, a magnetic hard disk or an integrated circuit (IC) memory card.

Claim 88. (Previously Presented) The recording method according to claim 80, wherein said analog video signal is an analog video signal having a combination signal of plural pseudo synchronization pulses and plural white peak signals across plural horizontal periods in a vertical blanking period of said analog video signal.

Claim 89. (Previously Presented) The recording method according to claim 80, wherein said analog video signal is an analog color video signal having an associated color burst signal

and wherein the phase of at least a portion of said color burst signal is changed from an original state.

Claim 90. (Previously Presented) The recording method according to claim 89, wherein said copy protection signal is a signal coded with plural bits, is located at a pre-set position of said analog video signal and is indicative of a limitation on recording.

Claim 91. (Currently Amended) A digital video signal recording method through which unauthorized copying of an analog video signal can be inhibited, comprising the steps of:

receiving said analog video signal, said analog video signal including a copy protection signal;

performing an analog-to-digital conversion on said analog video signal to generate digital video data;

compressing said digital video data to generate compressed video data;

detecting said copy protection signal included in said analog video signal;

generating copy management information according to a state of said copy protection signal detected in said step of detecting;

scrambling said compressed video data according to key information to generate scrambled video data; and

recording said scrambled video data with said key information, said key information being recorded at a pre-set position of a record medium;

whereby said copy management information is digital information that is generated based on an analog signal; said copy management information including an

indicator of whether copying of only digital video data generated from the received analog video signal is inhibited or copying of both digital and analog video data generated from the received analog video signal is inhibited.

Claim 92. (Previously Presented) The recording method according to claim 91, wherein said pre-set position of said record medium is located within a data area and/or a lead-in area of said record medium.

Claim 93. (Previously Presented) The recording method according to claim 92, wherein said pre-set position of said record medium is located within a header portion which is within said data area of said record medium.

Claim 94. (Previously Presented) The recording method according to claim 93, wherein said digital video data is partitioned into units and said key information is located in at least one of said units.

Claim 95. (Previously Presented) The recording method according to claim 91, wherein said key information corresponds to bit sequence data used to implement the scrambling.

Claim 96. (Currently Amended) A digital video signal recording method through which unauthorized copying of an analog video signal can be inhibited, comprising the steps of:

receiving said analog video signal, said analog video signal including a copy protection signal;

performing an analog-to-digital conversion on said analog video signal to  
generate digital video data;

compressing said digital video data to generate compressed video data;

detecting said copy protection signal included in said analog video signal;

generating copy management information according to a state of said copy  
protection signal detected in said step of detecting;

scrambling said compressed video data according to key information to generate  
scrambled video data;

appending said copy management information to said scrambled video data; and

recording said scrambled video data with said copy management information and  
said key information, said copy management information and said key information being  
recorded at a pre-set position of a record medium;

whereby said copy management information is digital information that is  
generated based on an analog signal; said copy management information including an  
indicator of whether copying of only digital video data generated from the received  
analog video signal is inhibited or copying of both digital and analog video data  
generated from the received analog video signal is inhibited.

Claim 97. (Previously Presented) The recording method according to claim 96, wherein  
said copy protection signal is a signal coded with plural bits, is located at a pre-set position of  
said analog video signal and is indicative of a copy generation limitation.

Claim 98. (Previously Presented) The recording method according to claim 96, wherein said pre-set position of said record medium is located within a data area and/or a lead-in area of said record medium.

Claim 99. (Previously Presented) The recording method according to claim 96, wherein said pre-set position of said record medium is located within a header portion which is within said data area of said record medium.

Claim 100. (Previously Presented) The recording method according to claim 98, wherein said key information corresponds to bit sequence data used to implement the scrambling.

Claim 101. (Currently Amended) A digital video signal recorder capable of inhibiting unauthorized copying of an analog video signal, comprising:

- an input terminal for receiving said analog video signal, said analog video signal including a copy protection signal;

- analog-to-digital converting means for converting said analog video signal to digital video data;

- compression means for compressing said digital video data to generate compressed video data;

- detecting means for detecting said copy protection signal included in said analog video signal;

- generating means for generating copy management information according to a state of said copy protection signal detected by said detecting means;

scrambling means for generating scrambled video data by scrambling said compressed video data according to said copy management information; and

encoding and modulating means for recording said scrambled video data and said copy management information on a record medium, said copy management information being recorded at a pre-set position of said record medium;

whereby said copy management information is digital information that is generated based on an analog signal; said copy management information including an indicator of whether copying of only digital video data generated from the received analog video signal is inhibited or copying of both digital and analog video data generated from the received analog video signal is inhibited.

Claim 102. (Previously Presented) The recorder according to claim 101, wherein said pre-set position of said record medium is located within a header portion of a data area and/or a lead-in area of said record medium.

Claim 103. (Currently Amended) A digital signal recorder capable of inhibiting unauthorized copying of an analog signal, comprising:

an input terminal for receiving said analog signal, said analog signal including a copy protection signal;

analog-to-digital converting means for converting said analog signal to digital data;

compression means for compressing said digital data to generate compressed data;

detecting means for detecting said copy protection signal included in said analog signal, said copy protection signal being a signal coded with plural bits, being located at a pre-set position of said analog signal and being indicative of a copy generation limitation;

generating means for generating copy management information according to a state of said copy protection signal detected by said detecting means;

appending means for appending said copy management information to said compressed data; and

recording means for recording said compressed data with appended copy management information, said copy management information being recorded at a pre-set position of a record medium;

whereby said copy management information is digital information that is generated based on an analog signal; said copy management information including an indicator of whether copying of only digital video data generated from the received analog video signal is inhibited or copying of both digital and analog video data generated from the received analog video signal is inhibited.

Claim 104. (Currently Amended) A digital signal recorder capable of inhibiting unauthorized copying of an analog signal, comprising:

an input terminal for receiving said analog signal, said analog signal including a copy protection signal;

analog-to-digital converting means for converting said analog signal to digital data;

compression means for compressing said digital data to generate compressed data;

detecting means for detecting said copy protection signal included in said analog signal, said copy protection signal being a signal coded with plural bits, being located at a pre-set position of said analog signal and being indicative of a copy generation limitation;

generating means for generating copy management information according to a state of said copy protection signal detected by said detecting means;

scrambling means for generating scrambled data by scrambling said compressed data according to said copy management information; and

encoding and modulating means for recording said scrambled data and said copy management information on a record medium;

whereby said copy management information is digital information that is generated based on an analog signal; said copy management information including an indicator of whether copying of only digital video data generated from the received analog video signal is inhibited or copying of both digital and analog video data generated from the received analog video signal is inhibited.

Claim 105. (Currently Amended) A digital video signal recording method through which unauthorized copying of an analog video signal can be inhibited, comprising the steps of:

receiving said analog video signal, said analog video signal including a copy protection signal;

performing and analog-to-digital conversion on said analog video signal to generate digital video data;

compressing said digital video data to generate compressed video data;

detecting said copy protection signal included in said analog video signal;



generating copy management information according to a state of said copy protection signal detected in said step of detecting;

scrambling said compressed video data according to said copy management information to generate scrambled video data;

encoding and modulating said scrambled video data and said copy management information to generate encoded and modulated data; and

recording said encoded and modulated data on a record medium such that a portion of said encoded and modulated data corresponding to said copy management information is recorded at a pre-set position of said record medium;

whereby said copy management information is digital information that is generated based on an analog signal; said copy management information including an indicator of whether copying of only digital video data generated from the received analog video signal is inhibited or copying of both digital and analog video data generated from the received analog video signal is inhibited.